Pre-Catalysed Lacquers High Build





A range of fast drying high build Basecoats and Lacquers with excellent levelling and easy sanding properties.

The Lacquers dry rapidly to give a finish with excellent flow and surface slip.

Always stir well and check sheen before use.

Sea	ler/Basecoat	ł

Pre-Catalysed Basecoat High-Build Pre-Catalysed Sealer for MDF edges

Lacquers

Pre-Catalysed Lacquer Matt Pre-Catalysed Lacquer Semi-Matt Pre-Catalysed Lacquer Eggshell Pre-Catalysed Lacquer Satin Pre-Catalysed Lacquer Semi-Gloss Pre-Catalysed Lacquer Off-Gloss Pre-Catalysed Lacquer Gloss

Number NL2501 NL2503

Number NM2502-0010 NM2502-0020 NM2505-0030 NM2502-0040 NM2502-0050 NM2502-0070 NM2502-0090

Sheen Viscosity N/A 68 - 72 secs 39 - 41 secs N/A

Sheen Viscosity 31 - 35 secs 10% 31 - 35 secs 20% 30% 31 - 35 secs 40% 31 - 35 secs 31 - 35 secs 50% 70% 31 - 35 secs 54 - 59 secs Gloss

Tinted Basecoats can be manufactured to suit most manufacturing requirements.

Tinted Lacquers can be manufactured to suit most manufacturing requirements.

Note: Pre-Catalysed Lacquers should not be applied over Sealers containing stearates.

SG / Coverage

Approx 0.91 / 7 square metres per litre

Application

Standard products are for conventional spray. Lacquers spray as supplied.

Air pressure: 35 - 45 psi Fluid pressure: 10 - 15 psi

Consult Becker Acroma Technical Department for use with other spraving techniques.

Special products are available for curtain and roller coating.

Drying

Touch Dry: 15 - 20 mins Sanding Recoating: 60 - 90 mins

These times may be reduced by force drying. Consult Becker Acroma Technical Department.

Packing: Overnight minimum

Thinners

Dual Thinners: NT2511

Cleaning Fluid

Cleaning Solvent NT2015. Use only for cleaning, and dry equipment after cleaning.

Retarder Solutions

Retarder Medium: DT2004 Retarder Strong: NT2514

Woodfiller

Nitrofilla

Non Fade Ground Stain: Suitable

Waterstain: Suitable

Stains must be dry before continuing with finishing system.

Limitations

Do not use over white or pastel shade enamels. A special non-yellowing Acid Catalysed Lacquer is available for this purpose.

Not recommended for use on horizontal working surfaces in laboratory, kitchen or bar situations.

Available in 5, 25 and 205 litre containers.

Health & Safety

Refer to Health and Safety Data Sheet for individual products.

Becker Acroma (Ireland) Limited Formerly Granyte Surface Coatings (Ireland) Limited

53 Robinhood Industrial Estate, Dublin 22, Republic of Ireland Tel: +353 (0)1 460 1445 Fax: +353 (0)1 460 1449 sales@becker-acroma-ire.com www.becker-acroma-ire.com

