

Partition Studs

Knauf 'C' Studs

Knauf 'C' Studs, Acoustic 'C' Studs, 'I' Studs and 'MW' Studs are the essential components for creating a number of warranted Knauf partition systems. When used with Knauf 'U' Channels these partition studs can be used to achieve a wide range of performance criteria and varying partition heights.

Galvanised lightweight steel section for use in non-load-bearing Knauf partition systems.

Compliance: EN 14195.



Dimensions (mm)				Material No.	Pack Details	
Gauge	Size/Webb	Length	Flange		Lengths/Pack	Kg (Approx.)
0.55	50	2400	35	243861	10	14
		2500	35	243863	10	15
		2700	35	243865	10	15
		3000	35	243869	10	17
		3600	35	243870	10	21
60	3000	35	243876	10	18	
		35	243877	10	22	
70	2400	35	243880	10	16	
		35	243887	10	18	
		35	243889	10	20	
		35	243898	10	24	
		35	243909	10	28	
92	3600	35	243923	10	26	
		35	243930	10	31	
146	2700	35	243847	10	27	
		35	243848	10	30	
		35	243849	10	35	
		35	243851	10	41	
0.70	70	3600	35	243917	10	30
		4200	35	243919	10	35
	92	3600	35	243933	10	34
		4200	35	243935	10	40
146	4200	35	243858	10	53	

Estimating Guide: 1.67 linear metres per m² partition (based on 600mm centres).