

SAFETY DATA SHEET

according to Regulation (EU) 2015/830

Page 1/5

Creocoat

Revision 4

Revision date 2019-10-17

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

| | |
|---------------------|----------|
| Product name | Creocoat |
|---------------------|----------|

1.2. Relevant identified uses of the substance or mixture and uses advised against

| | |
|--------------------|---|
| Product Use | [SU22] Professional uses: Public domain (administration, education, entertainment, services, craftsmen); [SU19] Building and construction work; [PC0] Other; [PROC10] Roller application or brushing; [ERC5] Industrial use resulting in inclusion into or onto a matrix; |
|--------------------|---|

1.3. Details of the supplier of the safety data sheet


| | |
|------------------|---|
| Company | Larsen Building Products Ltd |
| Address | 4 West Bank Road Belfast Harbour Industrial Estate Belfast BT3 9JL United Kingdom |
| Web | www.larsenbuildingproducts.com |
| Telephone | +44 (0)28 9077 4000 |
| Fax | +44 (0)28 9077 6945 |
| Email | t.moore@larsenbuildingproducts.com |

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

| | |
|---|---|
| 2.1.2. Classification - EC 1272/2008 | Asp. Tox. 1: H304; Skin Irrit. 2: H315; STOT SE 3: H336; Aquatic Chronic 2: H411; |
|---|---|

2.2. Label elements

| | |
|--|---|
| Hazard pictograms |  |
| Signal Word | Danger |
| Hazard Statement | Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways. Skin Irrit. 2: H315 - Causes skin irritation. STOT SE 3: H336 - May cause drowsiness or dizziness. Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects. |
| Precautionary Statement: Prevention | P261 - Avoid breathing dust/fume/gas/mist/vapours/spray. P264 - Wash thoroughly after handling. P271 - Use only outdoors or in a well-ventilated area. P273 - Avoid release to the environment. P280 - Wear protective gloves/protective clothing/eye protection/face protection. |
| Precautionary Statement: Response | P301+P310 - IF SWALLOWED: IF SWALLOWED: Immediately call a POISON CENTER/doctor/ . P302+P352 - IF ON SKIN: Wash with plenty of water/ . P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing. |

Creocoat

Revision 4

Revision date 2019-10-17

2.2. Label elements

| | |
|--------------------------------------|--|
| Precautionary Statement: Storage | P312 - Call a POISON CENTER/doctor/ /if you feel unwell. P321 - Specific treatment (see on this label). P331 - Do NOT induce vomiting. P332+P313 - If skin irritation occurs: Get medical advice/attention. P391 - Collect spillage. |
| | P403+P233 - Store in a well-ventilated place. Keep container tightly closed. P405 - Store locked up. |
| | P501 - Dispose of contents/container to |
| Precautionary Statement: Disposal | |

SECTION 3: Composition/information on ingredients

3.2. Mixtures

EC 1272/2008

| Chemical Name | Index No. | CAS No. | EC No. | REACH Registration Number | Conc. (%w/w) | Classification |
|---|-----------|-----------|-----------|---------------------------|--------------|---|
| Kerosene | | 8008-20-6 | 232-366-4 | | | Flam. Liq. 3: H226; Asp. Tox. 1: H304; Skin Irrit. 2: H315; STOT SE 3: H336; Aquatic Chronic 2: H411; |
| Bitumen (cutback hydrocarbon solvents) (Asphalt, petroleum fumes) | | 8052-42-4 | 232-490-9 | | | Asp. Tox. 1: H304; Aquatic Chronic 2: H411; |

SECTION 4: First aid measures

4.1. Description of first aid measures

| | |
|--------------|---|
| Inhalation | Harmful by inhalation. Inhalation may cause nausea and vomiting. May cause dizziness and headache. Move the exposed person to fresh air. Seek medical attention. |
| Eye contact | May cause irritation to eyes. Rinse immediately with plenty of water for 15 minutes holding the eyelids open. Seek medical attention if irritation or symptoms persist. |
| Skin contact | May cause irritation to skin. May cause dermatitis. Wash off immediately with plenty of soap and water. Remove contaminated clothing. Seek medical attention if irritation or symptoms persist. |
| Ingestion | Harmful if swallowed. Ingestion may cause nausea and vomiting. Ingestion is irritating to the respiratory tract and may cause damage to the central nervous system. DO NOT INDUCE VOMITING. If swallowed, seek medical advice immediately and show this container or label. |

SECTION 5: Firefighting measures

5.1. Extinguishing media

| | |
|--|---|
| | Use as appropriate: Carbon dioxide (CO2), Dry chemical, Foam. |
|--|---|

5.2. Special hazards arising from the substance or mixture

| | |
|--|---|
| | . Burning produces irritating, toxic and obnoxious fumes. |
|--|---|

5.3. Advice for firefighters

| | |
|--|---|
| | Wear suitable respiratory equipment when necessary. |
|--|---|

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

| | |
|--|---|
| | Ensure adequate ventilation of the working area. Eliminate all sources of ignition. Wear suitable protective equipment. |
|--|---|

6.2. Environmental precautions

| | |
|--|---|
| | Do not allow product to enter drains. Prevent further spillage if safe. |
|--|---|

6.3. Methods and material for containment and cleaning up

| | |
|--|--|
| | Absorb with inert, absorbent material. Transfer to suitable, labelled containers for disposal. Clean |
|--|--|

Creocoat

Revision 4

Revision date 2019-10-17

6.3. Methods and material for containment and cleaning up

| | |
|--|--|
| | spillage area thoroughly with plenty of water. |
|--|--|

SECTION 7: Handling and storage

7.1. Precautions for safe handling

| | |
|--|--|
| | Avoid contact with eyes and skin. Ensure adequate ventilation of the working area. Use explosion proof equipment. Keep away from sources of ignition - No smoking. Adopt best Manual Handling considerations when handling, carrying and dispensing. |
|--|--|

7.2. Conditions for safe storage, including any incompatibilities

| | |
|--|--|
| | Keep in a cool, dry, well ventilated area. Keep containers tightly closed. |
|--|--|

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1. Exposure Limit Values

| | | |
|---|--|--|
| Bitumen (cutback hydrocarbon solvents) (Asphalt, petroleum fumes) | WEL 8-hr limit ppm: - | WEL 8-hr limit mg/m3: 5 |
| | WEL 15 min limit ppm: - | WEL 15 min limit mg/m3: 10 |
| | WEL 8-hr limit mg/m3 total - inhalable dust: | WEL 15 min limit mg/m3 total - inhalable dust: |
| | WEL 8-hr limit mg/m3 total - respirable dust: | WEL 15 min limit mg/m3 total - respirable dust: |
| | | |
| | | |

8.2. Exposure controls

| | |
|---|---|
| 8.2.1. Appropriate engineering controls | Ensure adequate ventilation of the working area. |
| 8.2.2. Individual protection measures | Wear chemical protective clothing. |
| Eye / face protection | Approved safety goggles. |
| Skin protection - Handprotection | Chemical resistant gloves (PVC). |
| Respiratory protection | In case of insufficient ventilation, wear suitable respiratory equipment. |

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

| | |
|------------|----------|
| Appearance | Liquid |
| Colour | Brown |
| Odour | Aromatic |

SECTION 10: Stability and reactivity

10.2. Chemical stability

| | |
|--|---------------------------------|
| | Stable under normal conditions. |
|--|---------------------------------|

10.3. Possibility of hazardous reactions

| | |
|--|-------------------|
| | Oxidising agents. |
|--|-------------------|

10.4. Conditions to avoid

| | |
|--|-------------------------------|
| | Heat, sparks and open flames. |
|--|-------------------------------|

SECTION 11: Toxicological information

11.1.4. Toxicological Information

| | |
|--|-------------------|
| | No data available |
|--|-------------------|

Creocoat

Revision 4

Revision date 2019-10-17

SECTION 12: Ecological information

12.1. Toxicity

No data available

SECTION 13: Disposal considerations

General information

Dispose of in compliance with all local and national regulations.

SECTION 14: Transport information

Hazard pictograms



14.1. UN number

UN3082

14.2. UN proper shipping name

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

14.3. Transport hazard class(es)

| | |
|-----------------|---|
| ADR/RID | 9 |
| Subsidiary risk | - |
| IMDG | 9 |
| Subsidiary risk | - |
| IATA | 9 |
| Subsidiary risk | - |

14.4. Packing group

Packing group III

14.5. Environmental hazards

| | |
|-----------------------|-----|
| Environmental hazards | Yes |
| Marine pollutant | Yes |

ADR/RID

| | |
|-----------------|-----|
| Hazard ID | 90 |
| Tunnel Category | (E) |

IMDG

| | |
|----------|---------|
| EmS Code | F-A S-F |
|----------|---------|

IATA

| | |
|---------------------------------|-------|
| Packing Instruction (Cargo) | 964 |
| Maximum quantity | 450 L |
| Packing Instruction (Passenger) | 964 |
| Maximum quantity | 450 L |

SECTION 15: Regulatory information

Creocoat

Revision 4

Revision date 2019-10-17

SECTION 16: Other information**Other information****Text of Hazard Statements in Section 3**

Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways.
Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects.

Further information

The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process.