

# ROOFING COMPOUND TROWEL GRADE



Roofing Compound (Trowel Grade) is a solvent-based, thick, heavy-bodied, bituminous compound with excellent non-slump characteristics. It is principally used for repairing cracks in all types of roofs, including asphalt, bitumen felt, asbestos, cement, concrete, etc. Roofing Compound (Trowel Grade) is ideal for use as a glazing bar mastic on roof lights.

**EASY TO APPLY**  
**READY TO USE**  
**WATER-RESISTANT**  
**UNAFFECTED BY RAIN OR**  
**FROST IMMEDIATELY AFTER APPLICATION**



**TECHNICAL INFORMATION:**

<b>PRODUCT INFORMATION</b>	
<b>FORM:</b>	Black Paste
<b>MATERIAL:</b>	Bituminous Mastic
<b>PACKAGING:</b>	1kg, 2.5kg and 5kg metal paint tins
<b>CLEANING:</b>	Tools and spillages should be cleaned with white spirit.
<b>STORAGE:</b>	Store in manufacturer's containers in a cool, dry, well ventilated and frost-free place out of direct sunlight.
<b>SHELF LIFE</b>	12 months in manufacturer's unopened containers.
<b>FLASH POINT:</b>	39°C
<b>WATER RESISTANCE:</b>	Resistant to water when dried
<b>COVERAGE:</b>	0.7 m <sup>2</sup> /kg @ 1 mm

## **DIRECTIONS FOR USE:**

### **PREPARATION**

Surfaces should be clean, and free from grease, dust and loose debris. Lichen and moss should be removed and the surface treated with Larsen Concentrated Algicide. Roofing Compound Trowel Grade can be applied to damp not wet surfaces.

### **PRIMING**

Porous and dusty surfaces should be primed with Larsen Bitumen Primer, e.g. concrete, slate, steel, asphalt and corrugated iron.

### **APPLICATION**

Do not thin. Non-toxic, but adequate ventilation should be provided in confined areas. Apply with a steel trowel or putty knife, which may be lubricated with Turpentine substitute or White Spirit.

### **RESTRICTIONS**

Keep away from sources of ignition - no smoking. Use only in well ventilated areas. Avoid contact with eyes. Wash splashes off skin. Keep out of reach of children. Consult MSDS before use. Do not apply over tar based surfaces or surfaces that can rise above 65°C.