


MN-68-94 Discs depressed centre for concrete cutting

Flap discs type 42, with depressed centre, for cutting stone



Features & benefits

- High-quality silicon carbide provides long durability
- Bakelite bond, reinforced with a mesh, increases disc strength at high revolutions
- Abrasive grain size 30 increases stone cutting speed
- Disc hardness R (semi-hard) increases durability and cutting speed

Applications

- For cutting stones, lightweight concrete, ceramic breeze blocks and bricks
- Intended for using with angle grinders

Users

- Bricklayers
- Masons
- Pavers
- Fitters
- DIY enthusiasts

Corresponding products

- MN-93-004 Angle grinder 125 mm, 900 W
- MN-93-011 Angle grinder 230 mm, 2300 W
- MN-93-021 Angle grinder 115 mm, 600 W
- MN-93-022 Angle grinder 125 mm, 900 W
- MN-93-023 Angle grinder 125 mm, 1010 W
- MN-93-025 Angle grinder 230 mm, 2300 W
- MN-93-034 Angle grinder 125 mm, 1200 W

Technical properties

Index	Outer diameter of the disc [mm]	Internal diameter of the disc [mm]	Thickness of the convex disc [mm]	Box [pcs]	Outer [pcs]	Box weight [kg]	Outer weight [kg]	EAN
MN-68-941 *	115	22.23	3	25	200	1.62	13.0	5906757162853
MN-68-942	125	22.23	3	25	200	1.93	15.4	5906757162860
MN-68-943 *	180	22.23	3	25	100	4.3	17.2	5906757162891
MN-68-945	230	22.23	3	25	50	6.4	12.9	5906757162884

* Discontinued

Warnings



- Always use eye protection
- Always use gloves
- Always use dust mask
- Always use ear protection
- Always use safety workwear
- Maximum grinder operating speed is 80m/s