

IKO ULTRA T-O UNDERLAY

PRODUCT INFORMATION

IKO Ultra T-O Underlay is a fully bonded torch-applied, polyester reinforced, SBS modified bitumen underlay. It has an upper surface finish of sand and a thermo-fusible film on the underside.



Surface	Product Code
Sand	62150000

USE

This product is for use as an underlay within an IKO high performance built up roofing system specification.

The product must be applied by an IKO Approved Installer.

All work must be undertaken in accordance with the requirements of the specific information provided with the issued IKO Specification document, or guidance documents where applicable.

INDEPENDENT ACCREDITATION



2797-CPR-537586



0086-CPR-745786

The product carries a Declaration of Performance Certificate and is UK Conformity Assessed.

FEATURES & BENEFITS

High Performance – Exceptional dimensional stability and tensile strength.

High Specification – Forms part of an IKO flat roofing specification offer.

Polyester Reinforced – Robust carrier material

SBS Modification – Low temperature flexibility

COMPOSITION

Bitumen Modification:	SBS
Carrier:	Polyester
Form:	Roll
Colour:	Sanded
Length:	12m
Width:	1m
Mass/Weight:	3.167kg/m ²
Roll Weight:	38kg
Surface Finishes:	(upper) Sand (lower) Thermo-fusible film
Selvedge:	(upper) 75mm

INSTALLATION

Membrane Bond:	Torch applied
Lap Bond:	Torch applied

PERFORMANCE

For key product performance characteristics, please refer to the [IKO Declaration of Performance \(DoP\)](#)

DISCLAIMER

As this product is utilised within an Approved Contractor network and guided by an IKO Specification document, where omission or differing information exists the IKO Specification document will take precedence.

Whilst every precaution is taken to ensure that the information given in this literature is correct and up to date it is not intended to form part of any contract or give rise to any collateral liability, which is hereby specifically excluded.

IKO reserve the right to amend and/or withdraw this document without notice. Intending purchasers of our materials should therefore verify with the company whether any changes in our specification, application details, withdrawals or otherwise have taken place since this literature was issued.