

# R-DRG-V Ring collated nails with fuel cells and two types of valves in box - galvanised

Ring shank galvanised nails for timber framing, roofing and other timber applications



## Certificate



## Product information

### Features and benefits




- 34° angle collation with a clipped head ensures the nail is compatible with all leading manufactures tools
- Special coating at the base of the shank improves the drive of the nail and ensures a secure fixing
- Diamond point prevents the timber from splitting
- Waxed paper collation avoids deterioration in wet conditions
- [English]: łączenie taśmą plastikową
- 12um zinc coating provides protection according to Eurocode 5, service class 2 compliant
- Depending on the quantity of nails box contains 1,2 or 3 fuel cells

### Applications

- Timber frame stud work in timber framing industry
- Installation of battens and sheathing in roof construction
- Installation of soffits and other roof finishing elements
- Installation of wooden facades

### Base materials

- Timber
- Plywood
- Chipboard
- Wood



## Product commercial data

Index	Fastener diameter	Length	Head type	Shank type	Finish	Protection	Collation	Faste- ners per strip	Carton quantity	Fuel cells per car- ton	Box we- ight	Outer weight	EAN
	[mm]	[mm]						[pcs]	[pcs]	[pcs]	kg	kg	
R-DRG-2851-V	2.8	51	Clipped head	Ring	Silver Galvani- sed	Minimum 12 mi- crons	34° pa- per lami- nated	44	3300	3	9.00	9.00	59066754 64152
R-DRG-2863-V	2.8	63	Clipped head	Ring	Silver Galvani- sed	Minimum 12 mi- crons	34° pa- per lami- nated	44	3300	3	11.00	11.00	59066754 64169
R-DRG-2870-V	2.8	70	Clipped head	Ring	Silver Galvani- sed	Minimum 12 mi- crons	34° pa- per lami- nated	44	3300	3	12.04	12.04	59066754 64176
R-DRG-2875-V	2.8	75	Clipped head	Ring	Silver Galvani- sed	Minimum 12 mi- crons	34° pa- per lami- nated	44	3300	3	12.88	12.88	59066754 64183
R-DRG-3163-V	3.1	63	Clipped head	Ring	Silver Galvani- sed	Minimum 12 mi- crons	34° pa- per lami- nated	44	3300	3	12.96	12.96	59066754 64190
R-DRG-3175-V	3.1	75	Clipped head	Ring	Silver Galvani- sed	Minimum 12 mi- crons	34° pa- per lami- nated	44	2200	2	10.32	10.32	59066754 64206
R-DRG-3190-V	3.1	90	Clipped head	Ring	Silver Galvani- sed	Minimum 12 mi- crons	34° pa- per lami- nated	44	2200	2	12.13	12.13	59066754 64213